Department of Energy Policy Enforcement – Electric Tank Water Heaters

EFFECTIVE JANUARY 1, 2022 – Impacted Products Update

Effective January 1, 2022, electric tank water heaters with inputs less than or equal to 12kW will:

- require their efficiency be rated in terms of Uniform Energy Factor (UEF) and
- meet applicable NAECA III consumer (residential) efficiency requirements.

PHASED-OUT MODEL		AVAILABLE ALTERNATE MODEL	
E-SERIES ≤ 12KW		E-SERIES > 12KW	
E30A-3-G		E30A-15-G*	
E30A-6-G		E30A-15-G*	
E30A-9-G		E30A-15-G*	
E40A-3-G		E40A-15-G*	e c
E40A-6-G		E40A-15-G*	
E40A-9-G		E40A-15-G*	
E50(A)-3-G		E50(A)-15-G*	
E50(A)-6-G		E50(A)-15-G*	
E50(A)-9-G		E50(A)-15-G*	
E85(A)-6-G		E85(A)-15-G*	
E85(A)-9-G		E85(A)-15-G*	
E120(A)-6-G		E120(A)-15-G*	
E120(A)-9-G		E120(A)-15-G*	
ES-SERIES ≤ 12KW		ES-SERIES > 12KW	
ES50-6-G		ES50-15-G*	
ES50-9-G		ES50-15-G*	
ES85-6-G		ES85-15-G*	
ES85-9-G		ES85-15-G*	
ES120-6-G		ES120-15-G*	
ES120-9-G	3	ES120-15-G*	§
	O.E.		Ot:

^{*}Models shipped from factory greater than 12 kW.

This will result in changes to our residential and commercial electric tank water heater offerings. We will be stopping production on the following products:

All MHD Series, All ELD-C Series, 80 Gallon Tank, E and ES-Series ≤12kW.

Please reference the chart below for alternate electric water heaters.

PHASED-OUT MODEL	AVAILABLE ALTERNATE MODEL	
ELD-C SERIES	ELD SERIES – TB/**FTB	
ELD30-C	ELD30-TB/FTB	
ELD40-C	ELD40-TB/FTB	
ELD52-C	ELD52-TB/FTB	
ELDS30-C	ELDS30-TB/FTB	
ELDS40-C	ELDS40-TB/FTB	
ELDS52-C	ELDS52-TB/FTB	
ELD66-C	ELD66-TB/FTB*	
ELD80-C	ELD80-TB/FTB*	
ELD120-C	ELD120-TB/FTB*	
ALL MHD SERIES	MELD SERIES – TB/**FTB	
MHD75245	MELD75-TB/FTB*	
MHD85245	MELD85-TB/FTB*	
MHD105245	MELD105-TB/FTB*	
0		
80 GALLON ELECTRIC TANK	HYBRID ELECTRIC HEAT PUMP	
PROE80 2 RH93	PROPH80 T2 RH375-30 PROPH80 T2 RH375-SO	

^{**}FTB models (Fused Terminal Block) are standard for power requirements over 48 Amps (Amps calculation = watts/volts).

⁽A) denotes optional ASME rated model available. ASME Construction – E models (Immersion Thermostat) may be ordered with ASME certified construction. Add "A" after capacity designation. Example: E85-36-G becomes E85A-36-G.